

Telephone: 01787 226995
Fax: 0845 3016853
E-mail: mail@btmauk.com
Website: www.btmauk.com

Registered Office: Peershaws

Berewyk Hall Court White Colne Colchester Essex, CO6 2QB

## **Tyre Technical Advisory Committee**

Issued: 20/05/2010 Reviewed: 10/03/2015

## Euro look – tyre and wheel compatibility

In order to deliver their intended performance tyres must be fitted to a rim of appropriate width. There is a growing fashion to customise cars by stretching the tyres over excessively wide rims. See illustration below. Such fitment causes excessive distortion of the tyre sidewall and could lead to premature tyre failure. There is also a serious risk of the tyre being dislodged from the wheel rim under sudden cornering forces.


Vehicle manufacturers' original wheel and tyre equipment complies with the recommended fitments set out in BS ISO 4001: 2007. These data are also available in the standards manual published by the European Tyre and Rim Technical Organisation (ETRTO).

Aftermarket fitments that do not respect these recommendations may invalidate motor insurance and may contravene the Road Vehicles Construction & Use Regulation 27 (tyre not maintained in such condition as to be fit for the use to which the vehicle is being put), Regulation 63 (bodywork and spray suppression) and the Road Traffic Act section 40 (vehicle in dangerous condition).

Recommended rim widths calculated in accordance with BS ISO 4001: 2007 for the most popular tyre sizes are set out in the table below.

| Tyre size | Minimum rim width | Optimum rim width | Maximum rim width |
|-----------|-------------------|-------------------|-------------------|
| 205/55R16 | 5.5"              | 6.0"              | 7.5"              |
| 195/65R15 | 5.5"              | 6.0"              | 7.0"              |
| 175/65R14 | 5.0"              | 5.0"              | 6.0"              |
| 195/50R15 | 5.5"              | 6.0"              | 7.0"              |

Consumers are urged to consult the relevant tyre manufacturer before changing tyre or wheel sizes to ensure compatibility of the two components for the vehicle application.





The comments in this Position Statement are based on the general operating practices and environment found in the United Kingdom and the Republic of Ireland. No undertaking express or implied is given regarding the applicability of these comments to other operating environments. No part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, mechanical, photocopying, recording or otherwise, without the prior permission in writing of the publisher.

Although great care has been taken in the compilation and preparation of this Position Statement to ensure accuracy, the publisher cannot in any circumstances accept responsibility for errors or omissions or advice given in this publication.

Copyright ©BTMA 2015 Page 1 of 1 Published by the BTMA